



ZPMV8.E116573 Wiring, Printed Certified for Canada - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed Certified for Canada - Component

See [General Information for Wiring, Printed Certified for Canada - Component](#)

GGP ELECTRONICS GMBH

E116573

AN DER LEEGE 2-4

37520 OSTERODE AM HARZ, GERMANY

	Cond Width		Cond	SS/ DS/ DSO	Max Area Diam mm(in)	Solder		Max Oper Temp C	Flame Class	Meets UL796 UL796 DSR	C T I
	Min	Edge				C	sec				
Type	mm(in)	mm(in)	Thk mic(mil)			Limits C					
Multilayer printed wiring boards.											
868	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:105	DS	76.2 (3.0)	282	20	130	V-0	All	*
874	0.94 (0.037)	2.82 (0.111)	16.5 (0.65) Int:70	DS	12.8 (0.5)	270	10	130	V-0	All	4
879	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:102	DS	76.2 (3.0)	282	20	130	V-0	All	3
881	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:140	DS	76.2 (3.0)	282	20	130	V-0	All	3
Multilayer printed wiring boards (mass laminated).											
870	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
878	0.23 (0.009)	0.69 (0.027)	33 (1.30)	DS	25.4 (1.0)	260	20	105	V-0	All	-
880	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	260	20	130	V-0	All	*
Single layer printed wiring boards.											
869	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
882	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	120	V-0	▲	3

* - CTI marking is optional and may be marked on the printed wiring board.



Marking: Company name or file number and type designation and the Recognized Component Mark for Canada, . May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2016-10-21

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



ZPMV2.E116573 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

GGP ELECTRONICS GMBH

E116573

AN DER LEEGE 2-4

37520 OSTERODE AM HARZ, GERMANY

	Cond Width		Cond	SS/ DSO	Max Area	Solder		Max Oper	Meets	C	
	Min	Edge				Thk	Diam				Limits
Type	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer printed wiring boards.											
868	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:105	DS	76.2 (3.0)	282	20	130	V-0	All	*
874	0.94 (0.037)	2.82 (0.111)	16.5 (0.65) Int:70	DS	12.8 (0.5)	270	10	130	V-0	All	4
879	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:102	DS	76.2 (3.0)	282	20	130	V-0	All	3
881	0.08 (0.003)	0.08 (0.003)	16.5 (0.65) Int:140	DS	76.2 (3.0)	282	20	130	V-0	All	3
Multilayer printed wiring boards (mass laminated).											
870	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
878	0.23 (0.009)	0.69 (0.027)	33 (1.30)	DS	25.4 (1.0)	260	20	105	V-0	All	-
880	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	260	20	130	V-0	All	*
Single layer printed wiring boards.											
869	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	130	V-0	All	*
882	0.08 (0.003)	0.08 (0.003)	33 (1.30)	DS	76.2 (3.0)	282	20	120	V-0	▲	3

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2016-10-21

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:
1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".